

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A method of providing an authentication service, comprising:
with an authentication server, relating a user identity to a set of a plurality of authentication mechanisms, the user identity belonging to a user;
relating a type of transaction with a relying party to a level of authentication, the relying party reliant on the authentication service to authenticate the user before user access is provided to its service, program or information; and authenticating the user identity through at least one authentication mechanism in the set of the plurality of authentication mechanisms for the type of transaction, according to the level of authentication, wherein the user is granted or denied access to the service, program or information provided by the relying party.
2. (Original) The method as recited in claim 1, further comprising:
selecting the at least one authentication mechanism depending on the plurality of authentication mechanisms related with the user and the level of authentication.
3. (Original) The method as recited in claim 1, further comprising:
monitoring a series of authentications for the relying party to detect fraud.
4. (Original) The method as recited in claim 1, wherein the authentication mechanisms in the set of authentication mechanisms are part of a distributed system.
5. (Original) The method as recited in claim 3, wherein at least one of the authentication mechanisms is mobile.

6. (Original) A computer-readable medium having computer-executable instructions for performing the method as recited in claim 1.
7. (Currently Amended) A method of syndication, comprising:
offering an authentication service, the authentication service being capable of
authenticating a user identity with a plurality of authentication mechanisms, the user identity belonging to a user;[[,]]
rendering results of the authentication to at least one relying party, the relying party
reliant on the authentication service to authenticate the user before user access is
provided to its goods or services;[[, and]]
dynamically making an authorization decision; and
distributing the authentication service to the at least one relying party wherein the at least one relying party provides or does not provide a good or service to the user depending on the authorization decision.
8. (Original) The method as recited in claim 7, wherein the at least one relying party integrates the authentication service together with other offerings.
9. (Original) The method as recited in claim 7, wherein the dynamic authorization decision is based on a requested access level, authentication mechanisms used, and an account status.
10. (Currently Amended) The method as recited in claim 7, further comprising:
providing secure recovery from potential fraud without requiring re-registration of [[a]]
the user.
11. (Original) The method as recited in claim 7, further comprising:
charging the relying party for each authenticating event.
12. (Original) A computer-readable medium having computer-executable instructions for performing the method as recited in claim 6.

13. (Currently Amended) A method of registration, comprising:
 authenticating a user having a user identity;
 determining a level of user identity confirmation for a registration;
 receiving a new authentication mechanism from the user;
 receiving new authentication verification information; [[and]]
 storing user identity information, the level of identity confirmation, and the new
authentication verification information in a database; and
 sending the user identity information, the level of identity confirmation, and the new
authentication verification information.
14. (Original) The method as recited in claim 13, wherein authenticating the user is done by
a registration server.
15. (Original) The method as recited in claim 13, wherein authenticating the user is done by
a registration agent.
16. (Original) The method as recited in claim 13, wherein authenticating the user is
performed by using an authentication mechanism stored in the database.
17. (Original) The method as recited in claim 13, further comprising:
 receiving from the user, a request for registration.
18. (Original) The method as recited in claim 17, wherein receiving the request for
registration is done by an authentication server.
19. (Original) The method as recited in claim 17, wherein receiving the request for
registration is done by an authentication agent.

20. (Original) The method as recited in claim 13, wherein determining the level of identity confirmation for the registration is done by a registration server.
21. (Original) The method as recited in claim 13, wherein determining the level of identity confirmation for the registration is done by a registration agent.
22. (Original) The method as recited in claim 13, wherein receiving new authentication verification information is done by a registration server.
23. (Canceled)
24. (Currently Amended) The method as recited in claim ~~[[23]]~~ 13, wherein sending is done from a registration server to an authentication server.
25. (Currently Amended) The method as recited in claim ~~[[23]]~~ 13, wherein sending ~~the user identity information, the level of identity confirmation, and the authentication verification information~~ is done from a registration agent to a registration server.
26. (Currently Amended) The method as recited in claim ~~[[23]]~~ 13, further comprising sending pre-existing user information.
27. (Currently Amended) A method of providing an authentication service, comprising:
providing a list of supported authentication methods to authenticate at least one user;
receiving requirements for an authentication level from at least one relying party, the at least one relying party reliant on the authentication service to authenticate the at least one user before user access is provided to its service, program or information;
receiving a selection of authentication methods from the at least one user;
receiving identification information for the at least one user;

- producing a portfolio associated with the at least one user, the portfolio comprising the list of authentication methods, each authentication method in the portfolio meeting the selection of the at least one user, each authentication method in the portfolio supported by an authentication system, the list of authentication methods meeting the requirements for the authentication level from the at least one relying party; and
- relating the identification information to the portfolio for the at least one user.
28. (Original) The method as recited in claim 27, wherein receiving the selection is a subset of the list of supported authentication methods.
29. (Original) The method as recited in claim 27, further comprising:
storing the portfolio on an authentication server capable of providing the authentication service to the at least one relying party.
30. (Original) The method as recited in claim 27, further comprising:
providing a selection of authentication methods to the at least one user;
receiving at least one selected authentication method from the at least one user;
receiving authentication information required to perform authentication for each of the at least one selected authentication methods;
wherein the portfolio includes the authentication information.
31. (Original) The method as recited in claim 27, further comprising:
authenticating, by the authentication system, the at least one user to the at least one relying party.
32. (Original) The method as recited in claim 31, wherein authenticating the at least one user to the at least one relying party comprises:
providing a challenge to the at least one user;

accepting a response to the challenge from the at least one user;
examining the response to the challenge to ensure its authenticity;
comparing authentication information received by the at least one user to the portfolio
associated with the at least one user; and
communicating an authentication result to the at least one relying party.

33. (Original) The method as recited in claim 27, wherein the at least one relying party is an online pharmacy and the at least one user is a doctor.

34. (Original) The method as recited in claim 27, further comprising:
adding a new authentication method to the portfolio.

35. (Original) The method as recited in claim 34, wherein adding the new authentication method to the portfolio comprises:
authenticating the at least one user using an authentication method already in the
portfolio;
receiving authentication information for the new authentication method; and
storing the new authentication method and its authentication information in the portfolio.

36. (Original) The method as recited in claim 27, further comprising:
receiving notice of a potentially compromised authentication method in the portfolio;
authenticating the at least one user using an authentication method already in the
portfolio, but not using the potentially compromised authentication method; and
revoking the authentication information for the potentially compromised authentication
method in the portfolio associated with the at least one user.

37. (Original) The method as recited in claim 27, further comprising:
monitoring authentication events for the at least one user; and
detecting possible fraud for a suspect authentication method.

38. (Original) The method as recited in claim 37, further comprising:
 authenticating the at least one user using an authentication method already in the
 portfolio, but not using the suspect authentication method;
 communicating the possible fraud to the at least one user; and
 upon confirmation of fraud, revoking the suspect authentication method in the portfolio.
39. (Original) The method as recited in claim 37, further comprising:
 automatically revoking the suspect authentication method in the portfolio;
 wherein the possible fraud is potentially serious fraud.
40. (Original) A computer-readable medium having computer-executable instructions for performing the method as recited in claim 27.
41. (Original) A method of authentication, comprising:
 requesting, by a user to a relying party, a protected service;
 sending, by the relying party, a description of the request to an authorization server;
 determining, by the authorization server, a first level of assurance;
 sending, by the authorization server to an authentication server, the first level of assurance;
 requesting, by an authentication server, authentication from the user;
 entering, by the user, authentication information into an authentication device;
 sending, by the authentication device to the authentication server, authentication information;
 verifying, by the authentication server, the authentication information using authentication verification information stored in a portfolio in a database that is associated with the user;
 computing, by the authentication server, a second level of assurance;
 evaluating whether the second level of assurance is high enough;
 sending, by the authentication server to the authorization server, a first success message, upon determining the second level of assurance is high enough;

- verifying, by the authorization server, information from the authentication server;
- verifying, by the authorization server, that the user is allowed to perform the protected service;
- sending, by the authorization server to the relying party, a second success message, upon verification of the information from the authentication server and verification that the user is allowed to perform the protected service; and
- providing, by the relying party to the user, the protected service.
42. (Original) The method as recited in claim 41, further comprising:
- requesting, by the authentication server to the user, authentication using at least one additional authentication method, upon determining the second level of assurance is not high enough.
43. (Original) The method as recited in claim 42, further comprising:
- sending, by the authentication server to the authorization server, a first failure message and a reduced level of assurance, upon determining the user is unable to authenticate using the at least one additional authentication method;
- storing, by the authorization server, the reduced level of assurance;
- sending, by the authorization server to the relying party, a second failure message; and
- providing, by the relying party to the user, a third failure message.